MININD FORM NO. 64

Office Memorandum United States Government

· · · · · · · · · · · · · · · · · · ·	The Files - Contract 605, T.O. 2	DATE: 30 January 1959
ROM :		
U BJECT :	Conference Report - CS-8 Antenna	
	1. On 28 January 1959 a confer representatives of 605, T.O. 2. Those present at the conference of the	rence was held in Alcott Hall with to discuss progress on Contract conference were:
	DC-E/SEB 1 - OC-E/R+D Lef, OC-E/R+D-I C-SPS/EA - OC-E/R+D-EP 1 - OC-E/SEB OC-D/R+D-EP	EP
	antenna has been found to meet the	ion by the R+D Laboratory, the CS-8 design requirements for a collection

2.5×1

25X1

25X1

25X1

25X1

- 2. On the basis of an evaluation by the R+D Laboratory, the CS-o antenna has been found to meet the design requirements for a collection system antenna from 60 to 600 mc/sec. Although the results of the R+D Laboratory investigation may have been somewhat in error due to inadequate instrumentation and a poor test site, as pointed out by the results are sufficiently accurate to warrant acceptance of the antenna.
- 3. Because of the desire for one antenna covering 30 to 1,000 megacycles, possible modification of the CS-8 antenna was discussed. Artificial loading of the elements is unsatisfactory because of decreased high frequency performance. The possibility of using another antenna to cover 30 to 60 megacycles was considered. A filter crossover network would be used to couple the two antennas to a single receiver. Dr. will report soon on the feasibility of the above approach.
- 4. Several minor mechanical modifications were proposed by the writer to make installation and removal of the CS-8 antenna easier when used outdoors. Among these modifications were the following:
 - a) Provide a bearing assembly at the base of the outdoor mast and the guy support assembly to facilitate outdoor rotation.





- b) Drill holes in the mast-base support stakes to make their removal easier when driven hard ground. A screwdriver or metal rod could be inserted in the holes to provide handles.
- c) Supply a metal cap for the tapered feedline coaxial mount so as to prevent dirt and moisture from entering the connection.

	- •		
5. The antenna will be the minor modifications ment		for photography and	



25X1

25X1